



## DECLARATION OF PERFORMANCE

According to Regulation (EU) No.305/2011  
No. GJBB001/2

---

**HIDROGLET F WHITE**

---

**CE**

DECLARATION OF PERFORMANCE

1. Unique identification code of the product-type:  
**GJBB001**  
**EN 998-1:ZA.1, general purpose rendering mortar**
2. Intended use/uses:  
**This product is used for smoothing exterior wall and ceiling surfaces**
3. Manufacturer:  
**ADING AD Skopje, Novoselski pat (ul. 1409) br. 11, 1060 Skopje, R. North Macedonia**
4. Authorised representative:  
**/**
5. System or systems of AVCP:  
**System 4**
- 6a. Harmonised standard:  
**EN 998-1:2016**  
  
Notified body:  
**/**



## 7. Declared performances:

Essential Characteristics	Performance	Harmonised technical specification	
		MKC EN 998-1:2017	EN 998-1:2016
Compressive strength	<b>CS IV (<math>\geq 6 \text{ N/mm}^2</math>)</b>	MKC EN 998-1:2017	EN 998-1:2016
Capillary water absorption	<b>W<sub>1</sub></b>		
Water vapour diffusion coefficient.	<b><math>\mu \leq 15</math></b>		
Adhesion	<b><math>&gt; 0.5 \text{ N/mm}^2</math> – FP:B</b>		
Thermal conductivity	<b><math>\lambda=0.41 \text{ W/mK}</math></b>		
Reaction to fire	<b>Class A1</b>		

The performance of the product identified above is in conformity with the set of declared performances. This declaration of performance is issued, in accordance with the Regulation (EU) No. 305/2011, under the sole responsibility of the manufacturer identified in point 3.

Signed for and on behalf of the manufacturer by:

General Manager



Zoran Petrovski

Skopje, 03.11.2023

DECLARATION OF PERFORMANCE



## CE MARKING

Annex to DoP No. GJBB001/2

DECLARATION OF PERFORMANCE

CE	
ADING AD Skopje, Novoselski pat (ul 1409) br.11 1060 Skopje, North Macedonia 23 GJBB001/2 EN 998-1:2016 <b>HIDROGLET F WHITE</b> General purpose rendering mortar	
Compressive strength	<b>CS IV ( <math>\geq 6</math> N/mm<sup>2</sup> )</b>
Capillary water absorption	<b>W<sub>1</sub></b>
Water vapour diffusion coef.	<b><math>\mu \leq 15</math></b>
Adhesion	<b>&gt; 0.5 N/mm<sup>2</sup> – FP:B</b>
Thermal conductivity	<b><math>\lambda=0.41</math> W/mK</b>
Reaction to fire	<b>Class A1</b>

#### ECOLOGY, HEALTH AND SAFETY INFORMATION (REACH)

Information and advice on safe handling, storage and disposal of the chemical product are contained in the official Safety Data Sheet (SDS).

#### NOTE

The information and recommendations relating to proper storage, handling and end-use of Ading's products are given based on our best knowledge and experience. The differences in substrates and ambient conditions are not covered with this information. The user shall refer to the official technical data sheet. ADING reserves the right to change its products. The proprietary rights of third parties must be observed. All orders are accepted under current terms of sale and delivery.