



DECLARATION OF PERFORMANCE

According to Regulation (EU) No.305/2011
No. GJBA001/4

HIDROGLET F

CE

DECLARATION OF PERFORMANCE

1. Unique identification code of the product-type:
GJBA001
EN 998-1:ZA.1, general purpose rendering mortar
 2. Intended use/uses:
This product is used for smoothing exterior wall and ceiling surfaces
 3. Manufacturer:
ADING AD Skopje, Novoselski pat (ul. 1409) br. 11, 1060 Skopje, R. North Macedonia
 4. Authorised representative:
/
 5. System or systems of AVCP:
System 4
 - 6a. Harmonised standard:
EN 998-1:2016
- Notified body:
/



7. Declared performances:

Essential Characteristics	Performance	Harmonised technical specification	
		MKC EN 998-1:2017	EN 998-1:2016
Compressive strength	CS IV ($\geq 6 \text{ N/mm}^2$)	MKC EN 998-1:2017	EN 998-1:2016
Capillary water absorption	W₁		
Water vapour diffusion coefficient.	$\mu \leq 15$		
Adhesion	$> 0.5 \text{ N/mm}^2$ – FP:B		
Thermal conductivity	$\lambda=0.44 \text{ W/mK}$		
Reaction to fire	Class A1		

The performance of the product identified above is in conformity with the set of declared performances. This declaration of performance is issued, in accordance with the Regulation (EU) No. 305/2011, under the sole responsibility of the manufacturer identified in point 3.

Signed for and on behalf of the manufacturer by:

General Manager,

Zoran Petrovski

Skopje, 03.11.2023

DECLARATION OF PERFORMANCE



CE MARKING

Annex to DoP No. GJBA001/4

CE	
ADING AD Skopje, Novoselski pat (ul 1409) br.11 1060 Skopje, North Macedonia 15 GJBA001/4 EN 998-1:2016 HIDROGLET F General purpose rendering mortar	
Compressive strength	CS IV (≥ 6 N/mm²)
Capillary water absorption	W₁
Water vapour diffusion coef.	$\mu \leq 15$
Adhesion	> 0.5 N/mm² – FP:B
Thermal conductivity	$\lambda=0.44$ W/mK
Reaction to fire	Class A1

DECLARATION OF PERFORMANCE

ECOLOGY, HEALTH AND SAFETY INFORMATION (REACH)

Information and advice on safe handling, storage and disposal of the chemical product are contained in the official Safety Data Sheet (SDS).

NOTE

The information and recommendations relating to proper storage, handling and end-use of Ading's products are given based on our best knowledge and experience. The differences in substrates and ambient conditions are not covered with this information. The user shall refer to the official technical data sheet. ADING reserves the right to change its products. The proprietary rights of third parties must be observed. All orders are accepted under current terms of sale and delivery.