

## DECLARATION OF PERFORMANCE

According to Regulation (EU) No. 574/2014,  
 which refers to Annex III of the Regulation (EU) No.305/2011

No. GDAB001/1

---

**ADINGPOKS 1PV**

---

**CE**

DECLARATION OF PERFORMANCE

1. Unique identification code of the product:  
**GDAB001**
  2. Intended use/uses:  
**According to EN 1504-2:ZA.1e and EN 13813:SR-B2.0-IR4 epoxy primer for wet-damp concrete surfaces**  
**This product is intended for:**
    - **Moisture control (Method 2.2 according to EN 1504-9)**
    - **Increasing resistivity by limiting moisture content (Method 8.2 according to EN 1504-9)**
    - **Synthetic resin screed mortar for internal use**
  3. Manufacturer:  
**ADING AD Skopje, Novoselski pat (ul. 1409) br. 11, 1060 Skopje, R. North Macedonia**
  4. Authorised representative:  
 /
  5. System or systems of AVCP:  
**System 4**
  - 6a. Harmonised standard:  
**EN 1504-2:2004**  
**EN 13813:2002**
- Notified body:  
 /

## 7. Declared performances:

Essential Characteristics	Performance	Harmonised technical specification	
<b>According to EN 1504-2</b>		<b>MKC EN 1504-2:2006</b> <b>MKC EN 13813:2006</b>	<b>EN 1504-2:2004</b> <b>EN 13813:2002</b>
Capillary absorption and permeability to water	<b>w &lt; 0,1 kg/m<sup>2</sup>·h<sup>0,5</sup></b>		
Permeability to water vapour	<b>Class III, S<sub>D</sub> ≥ 50 m</b>		
Adhesion strength by pull-off test	<b>≥ 2,0 N/mm<sup>2</sup></b>		
<b>According to EN 13813</b>			
Impact resistance	<b>Class I ≥ 4 Nm</b> <b>After loading, no cracks, no delamination</b>		
Adhesive tensile strength	<b>Class B 2,0</b> <b>&gt; 2,0 N/mm<sup>2</sup></b>		
Emission of corrosive substances	<b>SR</b>		

DECLARATION OF PERFORMANCE

The performance of the product identified above is in conformity with the set of declared performances. This declaration of performance is issued, in accordance with Regulation (EU) No. 574/2014 which refers to Annex III of the Regulation (EU) No. 305/2011, under the sole responsibility of the manufacturer identified in point 3.

Signed for and on behalf of the manufacturer by:

General Manager,




Blagoja Donchev, Civ. Eng

Skopje, 22.10.2020

# CE MARKING

Annex to DoP No. GDAB001/1

DECLARATION OF PERFORMANCE

	
ADING AD Skopje, Novoselski pat (ul 1409) br.11 1060 Skopje, North Macedonia 20 GDAB001/1 EN 1504-2:2004 EN 13813:2002 SR-B2.0-IR4	
<b>ADINGPOKS 1PV</b> Epoxy primer for wet-damp concrete surfaces	
<b>According to EN 1504-2</b>	
Capillary absorption and permeability to water	<b>w &lt; 0,1 kg/m<sup>2</sup>·h<sup>0,5</sup></b>
Permeability to water vapour	<b>Class III, S<sub>D</sub> ≥ 50 m</b>
Adhesion strength by pull-off test	<b>≥ 2,0 N/mm<sup>2</sup></b>
<b>According to EN 13813</b>	
Impact resistance	<b>Class I ≥ 4 Nm</b> <b>After loading, no cracks, no delamination</b>
Adhesive tensile strength	<b>Class B 2,0</b> <b>&gt; 2,0 N/mm<sup>2</sup></b>
Emission of corrosive substances	<b>SR</b>

**ECOLOGY, HEALTH AND SAFETY INFORMATION (REACH)**

Information and advice on safe handling, storage and disposal of the chemical product are contained in the official Safety Data Sheet (SDS).

**NOTE**

The information and recommendations relating to proper storage, handling and end-use of Ading's products are given based on our best knowledge and experience. The differences in substrates and ambient conditions are not covered with this information. The user shall refer to the official technical data sheet. ADING reserves the right to change its products. The proprietary rights of third parties must be observed. All orders are accepted under current terms of sale and delivery.