



DECLARATION OF PERFORMANCE

According to Regulation (EU) No. 574/2014,
which refers to Annex III of the Regulation (EU) No.305/2011

No. GDCA002/3

PODING K RED

CE

1. Unique identification code of the product:

GDCA002

2. Intended use/uses:

**According to EN 13813 CT C50 F7 A9
Monolithic finishing coating based on cement, admixtures and high- quality fillers,
intended for mechanically loaded floors.**

3. Manufacturer:

ADING AD Skopje, Novoselski pat (ul. 1409) br. 11, 1060 Skopje, R. North Macedonia

4. Authorised representative:

/

5. System or systems of AVCP:

System 4

6a. Harmonised standard:

EN 13813:2002

Notified body:

/

DECLARATION OF PERFORMANCE





7. Declared performances:

Essential Characteristics	Performance	Harmonised technical specification	
		MKC EN 13813:2006	EN 13813:2002
Reaction to fire:	Class A1	MKC EN 13813:2006	EN 13813:2002
Release of corrosive substances:	CT		
Water permeability:	NPD		
Water vapour permeability:	NPD		
Compressive strength:	C50		
Flexural strength:	F7		
Wear resistance - BÖHME:	A9		
Sound insulation:	NPD		
Sound absorption:	NPD		
Thermal resistance:	NPD		
Chemical resistance:	NPD		

The performance of the product identified above is in conformity with the set of declared performances. This declaration of performance is issued, in accordance with Regulation (EU) No. 574/2014 which refers to Annex III of the Regulation (EU) No. 305/2011, under the sole responsibility of the manufacturer identified in point 3.

Signed for and on behalf of the manufacturer by:
General Manager,



Blagoja Donchev, Civ.Eng.


Skopje, 26.02.2021



CE MARKING

Annex to DoP No. GDCA002/3

DECLARATION OF PERFORMANCE

	
<p>ADING AD Skopje, Novoselski pat (ul 1409) br.11 1060 Skopje, North Macedonia 19 GDCA002/3 EN 13813 CT C50 F7 A9 PODING K RED Monolithic finishing coating based on cement, admixtures and high- quality fillers, intended for mechanically loaded floors</p>	
Reaction to fire:	Class A1
Release of corrosive substances:	CT
Water permeability:	NPD
Water vapour permeability:	NPD
Compressive strength:	C50
Flexural strength:	F7
Wear resistance - BÖHME:	A9
Sound insulation:	NPD
Sound absorption:	NPD
Thermal resistance:	NPD
Chemical resistance:	NPD

ECOLOGY, HEALTH AND SAFETY INFORMATION (REACH)

Information and advice on safe handling, storage and disposal of the chemical product are contained in the official Safety Data Sheet (SDS).

NOTE

The information and recommendations relating to proper storage, handling and end-use of Ading's products are given based on our best knowledge and experience. The differences in substrates and ambient conditions are not covered with this information. The user shall refer to the official technical data sheet. ADING reserves the right to change its products. The proprietary rights of third parties must be observed. All orders are accepted under current terms of sale and delivery.