

OPLATIN

Formwork release agent for timber, plastic and steel forms

Field of application:

It is used for protection of all kinds of forms, during execution of concrete works.

Properties:

- Enables easy separation of forms from the concrete;
- Does not leave any stains on the concrete surface; Better quality of the concrete surface;
- Resistant to atmospheric effects;
- Low consumption, economy;
- Protects the metal formworks against corrosion;
-

Technical features:

Appearance: Yellow-brown liquid
Bulk density: 0,8 - 0,9 g/cm³

Substrate preparation:

The formwork surface should be dry, clean and dust-free.

Application:

It is performed by means of a brush or else by spraying the formwork surface, with uniform movements aiming at ensuring complete uniform coverage.

Consumption:

0,02 - 0,05 kg/m²

Packing:

Plastic cans: 5 and 20 kg.
Drums: 180 kg.

Storage:

In original closed packing. Dry premises, at a temperature from minimum 5°C to maximum 40°C, protected against direct exposure to sun. Shelf life 12 months.

Health hazard:

It is necessary to avoid contact of the product with the skin. In a case of an accidental contact, the product should immediately be removed with water and soap. If the material has been splashed into the eyes, they should immediately be rinsed with a lot of water and medical assistance should be asked for.

It is necessary to provide ventilation of premises where work is performed.

They should not be used in the vicinity of some open fire or smoking during use.

We recommend for the way of application and the required quantities to be adjusted to the conditions of work.